



## **BOTO GCB7**

L-5S



- ▶ Smooth, extra deep tread pattern is specially designed for loaders, scrapers and other engineering machines which work underground mine alleys, tunnels or other harsh conditions
- ▶ Special cut resistant tread compound and formula and smooth, extra thick tread offers good performance, wear resistance and puncture resistance against ores and coal

SIZE	STAR RATING	TYPE	TRA CODE	STANDARD RIM	TREAD DEPTH (mm)	LOAD INDEX	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD AND INFLATION PRESSURE (kg/kpa)	
									50KM/H	10KM/H
12.00R24	★ ★ ★	TT/TL	L-5S	8.50	56	177A2	315	1275	7300/950	
14.00R24	★ ★ ★	TT/TL	L-5S	10.00W	56	188A2	375	1418	10000/950	
17.5R25	★ ★	TT/TL	L-5S	14.00/1.5	60	182A2	445	1399	8500/650	
18.00R25	★ ★	TL	L-5S	13.00/2.5	83	204A2	498	1673	16000/825	
23.5R25	★ ★	TL	L-5S	19.50/2.5	70	201A2	597	1617	14500/650	
26.5R25	★ ★	TL	L-5S	22.00/3.0	85	209A2	673	1798	18500/650	
29.5R25	★ ★	TL	L-5S	22.00/3.0	90	216A2	749	1921	22400/650	
29.5R29	★ ★	TL	L-5S	25.00/3.5	90	218A2	749	2023	23600/650	