



General wheel position for on/off road.  
Suitable for multiple-purpose transport  
on multiple road surface.

## Long Mileage Solution

- Optimize internal contour design to improve durability significantly.
- High abrasion tread compound combined with widened tread width to enhance expected mileage markedly.

## Low Failure Solution

- Specially designed pattern grooves can effectively protect against stone embed and avoid early damage.
- Big main blocks compound combined with reinforced block to enhance puncture resistance and cut resistance.
- Open shoulder design to enhance good heat dissipation capacity.

## Transport Efficiency Solution

- Hybrid pattern design to provide excellent traction and brake performance.



NO.	Size	Type	PR	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	14.00R20	TT	20	10.0	-	164/161J	-	20.0	295	375	1253	443	565
2	16.00R20	TT	22	11.25	-	174/171G	168/165L	20.5	380	438	1309	521	594
3	365/80R20	TT	16	10.00	10.00V	160K	-	20.0	314	364	1092	-	502
4	395/85R20	TT	14	10.00	10.00V,10.00	158J	-	25.0	328	396	1180	-	540