

HRL-4B

Time-proven bias tire for utility haulage applications

- Wide, flat tread radius for long life
- Solid centerline section for high-torque applications

TECHNICAL SPECIFICATIONS

Tire Dimension	Customized Construction Code	Load Range/ Ply Rating	Tread Depth (mm)	Tread Depth (32nds)	NA Material ID	AP Sales Code/ Material ID	LA Sales Code/ Material ID	EMEA Sales Code/ Material ID
16.00-25	4S	24	53	67	-	-	180175	-
16.00-25	2S	28	53	67	-	-	180329	-
16.00-25	4S	28	53	67	4803	-	180026	-
16.00-25	6S	28	53	67	-	-	180088	-
16.00-25	2S	32	53	67	202932	-	180394	-
16.00-25	3S	32	53	67	201571	-	180414	-
16.00-25	4S	32	53	67	181529	-	180420	-
16.00-25	6S	32	53	67	-	-	180413	-
18.00-25	4S	32	56	70	-	-	180027	600028
18.00-25	4S	40	56	70	-	-	180385	-
18.00-33	4S	32	56	70	-	-	180028	-
18.00-33	4S	36	56	70	189511	600307	180029	-
21.00-35	4S	36	56	70	4455	-	180030	-
21.00-35	4S	40	56	70	4450	-	180082	-
24.00-35	2S	42	58	73	192398	-	180184	-
24.00-35	4S	42	58	73	24643	-	180031	-
24.00-35	4S	48	58	73	189146	-	180387	-
24.00-49	4S	48	58	73	-	-	180206	-
27.00-49	2S	48	67	85	206900	-	180003	-
27.00-49	4S	48	67	85	203679	-	180151	-
30.00-51	2S	52	78	98	204599	-	180396	-
30.00-51	4S	52	78	98	-	-	180210	-
33.00-51	2S	58	83	104	193471	-	180407	-
33.00-51	3S	58	83	104	-	-	180191	-
36.00-51	4S	58	89	112	196774	-	180406	-

